SMARTBOX SG CONNECT

















READY TO CONNECT WITH:

- HYBRID INVERTER WITH BACK-UP POWER SUPPLY
- NON BACK-UP APPLICATIONS
- HEAT PUMP
- EV CHARGER
- WATER HEATER
- OTHER APPLICATIONS WITH SG READY CONTACT
- MODULE OPTIMIZERS (Only Box Type A)

Smart Box represents a revolution in home electrical networks. It is designed to combine all necessary components in one package, simplifying the installation. Moreover, it optimizes energy consumption and reduces costs, while the built-in safety switch and protective components ensure high safety level.

TECHNICAL SPECIFICATIONS

| Model | A163 | A363 | B163 | B363 | C300 |
|------------------------|-----------------------------------|---------------------|---------------------|---------------------|--------------------------|
| Rated voltage (Un): | 1x230 VAC, 50 Hz | 3x230 VAC, 50 Hz | 1x230 VAC, 50 Hz | 3x230 VAC, 50 Hz | 3x230 /400 VAC, 50 Hz |
| Rated current (In): | 63 A | 63 A | 63 A | 63 A | / |
| Protection (IP): | 54 | 54 | 54 | 54 | 54 |
| Dimensions (HxWxD): | 640x 420x 130 | 640x 420x 130 | 640x 420x 130 | 640x 420x 130 | 640x 420x 130 |
| TIGO: | YES | YES | NO | NO | NO |
| Standard: | SIST EN 61439-1 & SIST EN 61439-2 | | | | |